



"H.O. Slot Car Racing ... The World's Fastest Motorsport"



Overview - The materials in this rulebook are copyright ©1975 - 2026 H.O. Professional Racing Association (HOPRA). All rights reserved. All rights not expressly granted here are reserved. HOPRA has no control and is not responsible for any offer, product or service provided by the participating companies. HOPRA does not recommend or otherwise endorse any specific manufacturer. All materials, including, without limitation, the logos, design, text, graphics are Copyrighted by each company or manufacturer mentioned in this rulebook.

Copyright information - All of the contents of this rulebook are protected from copying under U.S. and international copyright laws and treatises. Any unauthorized copying, alteration, distribution, transmission, performance, display or other use of this material without the express written consent of HOPRA is prohibited.

Consents - Requests for consents or approvals should be made in writing and directed to the HOPRA National Director. See website for contact information. www.hopra.net

Use of information - HOPRA hereby authorizes you to view, copy, print and distribute materials available in this rulebook provided that (1) the materials are used for internal informational purposes only; (2) the above copyright notice appears on every copy of the material and any portion thereof; and (3) no content or related graphics are modified or altered in any way. Any rights not expressly granted herein are reserved by HOPRA.



OFFICIAL NATIONAL RULES

2026

Revised 12/29/26



1. DEFINITIONS	3
2. GENERAL RULES	5
3. BOX STOCK CAR CLASS	7
4. SPEC STOCK CAR CLASS RULES	8
5. SPEC RACER CAR CLASS RULES	9
6. SPEC JET CAR CLASS RULES	10
7. VINTAGE T-JET CAR CLASS RULES	11
8. SUPER STOCK CAR CLASS RULES	13
9. MODIFIED CAR CLASS RULES	14
10. COMPRESSOR MODIFIED POLYMER MODIFIED CAR CLASS RULES	15
11. NEO MODIFIED CAR CLASS RULES	17
12. UNLIMITED CAR CLASS RULES	18
13. GRAVITY CAR CLASS RULES	18
14. CONCOURS D'ELEGANCE RULES AND PROCEDURES	19
15. BEST APPARING RACE CAR RULES AND PROCEDURES	20
16. DRIVER RULES	21
17. RACING RULES AND PROCEDURES	22
18. TRACK AND EQUIPMENT RULES	24
19. TRACK AND EQUIPMENT GUIDELINES	25
20. NATIONAL CHAMPIONSHIP RACE RULES AND PROCEDURES	26
21. OFFICIALS & MEMBERSHIPS	27
22. NATIONAL EXECUTIVE COMMITTEE PROCEDURE GUIDELINES	29
23. NATIONAL EXECUTIVE COMMITTEE PROCEDURE RULES	29
24. NATIONAL EXECUTIVE COMMITTEE ORGANIZATIONAL CHART	30
25. APPENDIX GUIDELINES	31

A. Stock armature: The armature as it comes from the original manufacturer. Must be readily available. It must be a production machine wound red wire with crimp/folded/welded tabs. No post manufacture rewinding, rewinding, or soldered tabs. The amateur must contain one shaft, 14 laminations, 2 plastic heat shields, and one commutator. The commutator must contain separate components, which include the three (3) separate copper or metal segments covering one (1) solid plastic insulator held together by one (1) plastic ring or band. No high temperature one piece molded, ceramic, or bonded commutators are allowed.

B. Hot Stock armature: A modified Stock armature that may be exposed, have the commutator tinned, outside of the laminations dried and be advanced timed. Small cuts or drill marks may be made for balancing only. No machining.

C. Chassis: H.O. scale slot car "frame" designed for current H.O. slot car track competition as is produced by the manufacturer and adheres to all other rules. HOPRA Approved chassis are outlined in each class. Chassis and chassis components must be:

- a. Made from a plastic type or other material and cannot be metal, magnetic, or conductive.
- b. Injection molded and no after production machining is allowed except where allowed per class rules.
- c. All Magnets are considered part of the chassis.
- d. a. and b. above do not apply to the chassis clips - Any chassis clip used to hold the car together that is metal, magnetic, or conductive must not touch the magnets or affect the magnetic field.
- e. The endbell, magnet retaining clip(s), bulkheads, and timing brackets are not considered part of the chassis and must follow the same guidelines as above (a and b).

D. General rule #: All new cars, chassis and magnet sets must be submitted no later than October 15th to be considered for approval for the following years National Championship Race. The submitted car, chassis or magnet(s) must be the final-produced product (marketing packaging may be excluded) that is solid. If for any reason a manufacturer does not submit a new car/chassis/magnet set, a member of the HOPRA Executive Committee may purchase the item for their address, phone number, name of item purchased, its price and the total price paid, must accompany all items submitted to the Committee for review and approval. An original purchase receipt that shows the name of the vendor, submission to the Committee for review and approval, and a copy of the original purchase receipt that shows the vendor's name and address, name of item purchased, its price and the total price paid, must accompany all items submitted in this manner.



- January 15th - Final rule book completed and posted.
- June 1st - All items to be added to the agenda for the National Open Meeting.
- October 15th - Car, Chassis and Magnet submitted deadline date.
- (Manufacturer physically notified within 3 weeks of submitting)
- December 15th - Outstanding rule proposals and revisions shall be finalized.

24. NATIONAL EXECUTIVE COMMITTEE ORGANIZATIONAL CHART

National Director+
Assistant Director+ Membership Director+ Information Director+
State/Regional Representatives++
Manufacturer Representatives (non-voting positions)+++

+Filled or voted in from within the current National Executive Committee members.

++Voted in by current state/regional HOPRA members.

+++Appointed by manufacturers (Scale Auto/BSRT ©, Slottech ©, Wizzard ©, RPMs ©, Viper Scale Racing ©)

DUTIES

National Director – Oversees the general operation of the organization within the procedural guidelines of the Official HOPRA National rules.

Assistant Director – Assists the National Director with day-to-day organizational operation and stands in for him/her when requested.

Membership Director – Receive membership applications, issues packets, maintains current membership list and makes it available to all state/regional representatives.


Information Director – Creates, oversees, and updates website, print materials, audio/video technology, network operations, lap counting software brackets, and any other items as requested by Directors and Representatives.

State/Regional Representatives – Voice for the current membership in their state/region, present and vote on new rule proposals.

Manufacturer Representatives – Gives State/Regional Representatives information on new products, concerns of manufacturers and informs manufacturers of rule proposals and any other information. Included in National Executive Meetings (for the parts submission portion of the agenda) to provide answers/feedback on products. (Non-voting position)

1. DEFINITIONS

1. Concours d'Elegance	A competition to determine the best-looking cars.
2. Best Appearing Race Car	A competition to determine the best-looking cars that are entries in a racing event.
3. Cut	Sanding, melting, trimming, i.e., to reduce. (This does not include natural wear caused by track rails.)
4. Entry	One who has paid the entry fee and whose car has passed the technical inspection.
5. Extra Magnets	Any <u>stock</u> magnets that are not armature magnets.
6. Flux Collectors	Shim (not including a car's armature and magnets) that strengthens a magnet for horsepower or handling purposes, and/or collects magnetic flux for handling purposes.
7. General Rules	Rules which are applicable to all car classes.
8. Readily Available	Mass produced for HO slot car racing and obtainable by October 15th prior to the year's National Championship Race.
9. Scratch built	Chassis or individual car parts made by hand and are not mass produced.
10. Shall	Mandatory.
11. Shim	Material that exhibits magnetic attraction to a magnet.
12. Shunt(s)	A direct permanently joined connection between the pickup shoe to the motor brush.
13. Stock	Any part or condition that normally comes with the car as manufactured.
14. Stock Replacement	Part that is designed to replace an existing Stock part. The stock replacement part must fit without modification to the car or chassis and must be available by April 15 th .
15. Electrical systems	Any component that contains current while power is applied to the car.
16. Bottom Surface	The portion of any part of the car that is closest to the track when the car is placed in an operational mode on the track after the car is built.
17. Polymer Magnets	Bonded magnets that are made from Cobalt or Neodymium powder mixed with an epoxy, plastic, or polymer binder. The manufacturing process involves combining Neodymium or Cobalt powder with an epoxy, plastic, or polymer binder and compressing the mixture in a press and curing it to final shape with no subsequent machining allowed (except where indicated per car class).
18. HOPRA Approved	The Executive Committee has the right to declare the legality of a product.
19. Stock armature	Armature as it comes from the original manufacturer. Must be readily available. Minimum ohms requirements are set per class. (See Appendix for more details)
20. Hot Stock armature	A modified Stock armature. Minimum ohms requirements are set per class. (See Appendix for more details)
21. Car(s)	A fully assembled HO scale 4-wheeled vehicle as it is produced by its manufacturer and adhering to all HOPRA rules. These 'Vehicles' must be able to run on HO tracks without additional parts added after the manufacturing and assembly processes have been completed. The 'car' must have an option of being sold fully assembled or in kit form which includes all the parts necessary to complete one, single, fully assembled, scale vehicle.
22. Chassis	HO scale slot car "frame" designed for current HO slot car track competition as it is produced by the manufacturer and adheres to all other rules. HOPRA Approved chassis are outlined in each class. (See Appendix for more details)





22. NATIONAL EXECUTIVE COMMITTEE PROCEDURE GUIDELINES

- Proposals for all rule revisions and/or new rules shall be submitted to the members of the National Executive Committee in writing and forwarded directly to the National Director no later than June 1st for voting at that current year Nationals. It is then the National Director's responsibility to distribute the proposals to all active National Executive Committee members for discussion and testing. Proposals submitted after this date must be submitted by at least three (3) members of the National Executive Committee to be considered for an emergency vote.
- After June 1st all submitted rule proposals will be distributed by the National Director to the National Executive Committee members for comments. It is recommended that the National Executive Committee members be given a time period of no less than two (2) weeks to review the proposals and return any comments back to the National Director. The National Director will then be responsible for distributing all pertinent comments to all active National Executive Committee members. The comment procedure may be waived as seen fit by the National Director if deadlines do not allow time for the comment process.
- It is recommended that National Executive Committee members be given a time period of no less than two (2) weeks to review rule proposals and/or comments before being required to cast their votes. Votes on rule proposals to be forwarded by National Executive Committee members directly to the National Director, if less than two (2) weeks to distribute the votes and results to all active National Executive Committee members.

23. NATIONAL EXECUTIVE COMMITTEE PROCEDURE RULES

- An absolute majority vote shall be necessary to pass a proposal. Abstentions shall not be counted as eligible votes and will be counted as a violation of Section 2, #7. Only in an emergency situation as declared by the National Director, when time deadlines do not allow for a re-vote, can this procedure be waived. In the event of an emergency situation where a re-vote exists, the National Director will be allowed to break the tie vote. Definition of an emergency situation requires 50% + 1 of the total potential voters in order to pass.
- A 2/3 majority vote by the active members of the National Executive Committee shall be necessary to overturn a decision rendered by the National Director.
- In the event that the National Director cannot fulfill the term of office, the Assistant National Director shall be appointed to take over the office of National Director for the remainder of the current term. The National Executive Committee shall elect from within itself, a new Assistant Director by a simple majority vote.
- Outstanding rule proposals, revisions, and new parts submissions shall be voted on by the National Executive Committee no later than December 15th of that year.

23. Chassis clip	Clip used to hold the car together and follow Appendix guidelines.
24. Magnet	Clip used to retain/hold the magnets and/or bushings/bearings in place in the chassis. Not considered to retain/hold the magnets in place. Must be readily available and follow Appendix guidelines.
25. Bulkhead	Bulkheads between various parts of the car that are sole and help the bushings/bearings and may also structure by increasing girth. Contains and/or holds the bushings/bearings. Not considered part of the chassis or rear structure. Not considered part of the chassis. Must be readily available and follow Appendix guidelines.
26. Endbell	Endbell holds the electrical system and/or bushings/bearings. Not considered part of the chassis. Must be readily available and follow Appendix guidelines.
27. Timing bracket	Designed with the purpose of creating adjustable timing for the endbell and may also retain/hold chassis. Must be readily available and follow Appendix guidelines.
28. T-jet Top Plate	Forms the upper housing of the "package motor" enclosing the main engine assembly. Also supports the gear plate assembly, which transfers power from the armature to the axle. Not considered part of the chassis. Must be readily available and follow Appendix guidelines.

9. The HOPRA National Rules shall be published no later than January 15th and be effective for that year's National Championship Race.
10. The National HOPRA Membership packages will include the following:

Membership Package	Family Member Package	Lifetime Member Package
\$15.00 (yearly expires June 1st each year) <ul style="list-style-type: none"> ○ Digital Rulebook ○ Membership Card ○ Nationals Flyer Mailings ○ Newsletters (if published) ○ Member Discounts ○ 2- HOPRA Stickers 	\$5.00 (For additional immediate family members) <ul style="list-style-type: none"> ○ Membership Card ○ Nationals Flyer Mailings ○ Newsletters (if published) ○ Member Discounts ○ 1- HOPRA Stickers 	\$325.00 (nontransferable) <ul style="list-style-type: none"> ○ Digital Rulebook ○ Membership Card including an exclusive permanent member ID number. ○ Numbered Lifetime plaque ○ One free support class entry per year, regardless of racer status ○ Nationals Flyer Mailings ○ Newsletters (if published) ○ Member Discounts ○ 2- HOPRA Stickers ○ Other sponsored merchandise *where available

11. An annual accounting of HOPRA memberships shall be presented and published by the Membership Director or an appointed Senate Member each year at the National Championship Races.
12. The content and Logos in this rulebook are copyrighted symbols of H.O. Professional Racing Association (HOPRA). See page 32 for more information.

2. GENERAL RULES

1. All magnets must be "HOPRA Approved" and made from ceramic or polymer magnet material only.
2. No freak or irregular magnets shall be allowed. Ceramic magnets must be within 5% of the standard set submitted. Motor and Traction magnets must be under a set Gauss limit by car class. See car classes for gauss limit information.
3. The number of armature magnets used per car cannot exceed the stock number and cannot be more than two. Each magnet cannot exceed more than .0233in^3 and must be a minimum of .0175in^3 of total volume.
4. The number of extra magnets used per car cannot exceed the stock number and cannot be more than two. Each magnet cannot exceed .0141in^3 and must be minimum of .0125in^3 of total volume.
5. The number of flux collectors used per car cannot be more than stock.
6. Any car, which contains more than two magnets, shall not be allowed any flux collectors.
7. The chassis entered must be HOPRA Approved, with magnets being part of the chassis and cannot be substituted. Bulkheads, chassis clip(s), endbell, magnet retaining clip(s), and timing brackets are part of the car and can be replaced after qualifying. The body cannot be substituted except for same color conflicts and at the tech inspector's discretion and approval.
8. All cars/chassis must be readily available and HOPRA approved. See individual class rules for legal chassis.
9. All new cars, chassis and magnet sets must be submitted no later than October 15th to be considered for approval for the following year's National Championship Race. **(See appendix for more details)**.
10. Magnets submitted for "HOPRA Approval" are to be considered the "standard" set regarding all technical inspection questions. Meters throughout the organization will be calibrated using these standard magnets provided. These standard sets are to be identical to what is readily available.
11. Chassis/Cars submitted for "HOPRA Approval" are to be considered the "Standard" regarding all technical inspection questions. Changes to the original "Standard" design spec chassis shall be resubmitted for "HOPRA Approval" and will be considered a new chassis or car. All chassis must be molded and no after production machining is allowed except where specifically allowed by class rules.
12. No broken chassis will be allowed to enter the race except for body mounts and/or pick up shoe bumper guards. Guide pin bumper must not be broken.
13. A non-adhesive, non-magnetic, separate, and easily removable material can be used to restrict the movement of magnets in the chassis except for where not allowed per class rules.
14. The minimum allowable wheelbase is 1 1/4 (1.250) inches.
15. The maximum allowable width of the car is 1 5/16 (1.3125) inches.
16. The maximum allowable length of the entire car is three (3.00) inches.
17. Only one guide pin per car shall be allowed.
18. The maximum allowable lateral movement of the front axle is 1/32 (.03125) inch and may not exceed general rule 15 when extended to the furthest point.





21. OFFICALS & MEMBERSHIPS

20. NATIONAL CHAMPIONSHIP RACE RULES AND PROCEDURES

1. The National Championship Race shall use the Official HOPRA National Rules as voted on by the National Executive Committee.
2. Bids for future National Championship Events shall be submitted on the official National Championship Race bid form.
3. Bids for the following year's National Championship Race shall be submitted to the National Director prior to the present year's National Championships. Incomplete bids may be submitted (complete bids are preferred). Bids for future National Championship Races may be submitted at any time and will be kept on file for future use.
4. In the event that no bids are received for the next year's National Championship Race, the National Director shall appoint a committee composed of National Executive Committee members to find an appropriate site for holding next year's National Championship Race.
5. National Championship races shall be held on standard HO scale racetracks. No form of "trick" tracks shall be allowed. Any Box Stock car shall be able to negotiate all lanes of the track. If a track is to be used that is not of plastic track (i.e., Tyco, Aurora T-Jet, A/FX), the dimensions of the track (track material, rail type, rail width, rail height, space between rails, slot width, slot depth, space between slots, etc.) must be included in the National Championship publications.
6. It shall be the responsibility of the HOPRA Information Director to coordinate the publication of the HOPRA National Championship Race Report. The Race Promoter(s) and HOPRA National Executive Committee shall be required to furnish all assistance deemed necessary by the HOPRA Information Director. This report shall contain brief summaries of each Championship or other event held at the year's HOPRA Nationals. The finishing order and final lap totals for each participant in each Championship Event shall be included. The liberal use of photographs and graphics is encouraged. This report shall be mailed to all participants and sponsors involved with the HOPRA Nationals, and to all slot car racing trade publications, within 45 days after the conclusion of the HOPRA Nationals.
7. An award for "National Drivers Championship" for the best racer at Nationals. Take the three (3) best finishes from any one driver for the best average finish position for a National Class. This would encourage more participation.
8. Each class payout at a minimum would be a percentage (1st 40%, 2nd 30%, 3rd 20%, 4th 10%) based on the number of entries per class; HOPRA would receive a percentage (10%-20% + \$5 per entry) of the total entries per class before calculating the final payout for each class.

3. BOX STOCK CAR CLASS

This class is divided into two divisions: Inline Motor cars and Can Motor cars.

Eligible Inline Motor cars are: Tomy SG+, AFX Mega G, LifeLike M-chassis, Tyco/Mattel 440x2, Auto World Super III, JAG Hobbies TR-3/NC-2/PR5

Eligible Can Motor cars are: Tomy SRT/Turbo, LifeLike T-chassis, AFX Mega G+, HC Slots Super 7

Rules for both divisions:

1. Only allowed changes to stock, out-of-the-package car is the addition of any non-coated solid silicone, rubber, or urethane replacement rear tires and any double or single flanged replacement wheels.
2. Every part will be exactly as it comes from the original manufacturer for that particular car type/model, including all gears, axles, pickup shoes, pickup shoe springs, motor brushes and motor springs. No cutting or reaming of chassis, axle holes or any bushings. Axle diameter and length must remain stock. No truing, lightening or other modifications to front wheels/tires. See #9 for minimum front tire size for each car type/model. Rear rims and slip-on tires, per #1, are only allowable changes.
3. Armatures will be in factory stock condition as it comes from the original manufacturer for that particular car type/model. No tampering with stock condition.
4. Absolutely no cutting, lightening or any other modification allowed to car's body. Re-paints are permitted. Body types (i.e., stock car, sports car, open wheel) are to be determined on a race-by-race basis.
5. Polishing and lubricating of metal components are permitted.
6. Removal of protective plastic heat shields is permitted.
7. Guide pin may be trimmed for clearance purposes.
8. Pick-up shoe spring tension may be adjusted.
9. Minimum diameter for front tires, per particular car type/model:
 - a. Tomy SRT, Super 7, and all JAG -- .385
 - b. AFX Mega G and Mega G+ -- .375
 - c. Tomy Super G+ -- .385
 - d. Tomy Turbo -- .380
 - e. LifeLike T-chassis -- .370
 - f. LifeLike M-chassis -- .370
 - g. Auto World Super III -- .410
 - h. Tyco/Mattel 440x2 -- .410





- All tracks used for HOProA competition should be situated so as to provide for complete marshalling positions. These positions should not interfere with drivers or the track.
- All tracks used for HOProA competition should have padded retaining walls.
- All tracks used in HOProA competition should have padded retaining walls.
- The following are recommended lane colors from inside to outside at drivers's station starting from left to right: 6 Lane yellow, 4 Lane yellow, 6 Lane blue, 4 Lane blue, 6 Lane orange, 4 Lane orange, 6 Lane green, 4 Lane white, 6 Lane red, 4 Lane white, 6 Lane red.
- The following are recommended lane stripe of 3/16 or narrower: 6. Control hookups should be white, black, and red from left to right.

Manufacturer	Part #	Description	Magnets
BSRT	#277	G-Force HD Motor	G-Force Traktion
#280	#284	G-Force Motor	G-Force Traktion
Slotech	#81C	G6 Motor	G6 Traktion
Wizzard	WS60	Sock Storm Motor	Fusion Polymer Motor
22737	12000	Pro 4 Motor	Fusion Polymer Traktion
22736	12001	Pro 4 Transition	Fusion Polymer Motor
Viper Scale Racing	22816	Pro 4 Maxi Transition	Viper Pro 4trm SR Motor
11024	11135	Pro 4 Transition	Viper V3 Slip Traktion
4.	RPMS	RPMSHF-LDMA4	Hyper-Force Motor
3.	RPMS	RPMSHF-L4-T	Hyper-Force Traktion
2.	RPMS	RPMSHF-LDMA-SB	Hyper-Force Motor Magneits (Skinny Bar)
1.	RPMS	RPMSHF-LDMA-HR	Hyper-Force Motor Magneits (High RPMs)

HOProA Approved Compreression Molded Magnets for Spec Stock, Spec Jet, and Spec Racer Cars

- Chassis must be stock and cannot be modified in any way except to cut off molded in body posts and drill holes for axle retainers.
- All magnets must be "HOProA Approved" stock ceramic or "compreression molded polymer" and cannot be cooled down period and at the lowest point on each magnet as it runs parallel to the rail. Any reading above these out gauss reading of the traction or magnet shall not exceed the following criteria. This is taken after a 5 min cool down period and at the lowest point on each magnet as it runs parallel to the rail. Any reading above these
- figures will be cause for disqualification or refection at each.

Legal chassis are: BSRT G3/G3R/G3RS/G3RSB, Slotech T1/T2/T3, Wizzard Storm/Fusion, Viper V1/V3, RPMS Ghost Cat

19. TRACK AND EQUIPMENT GUIDELINES

4. SPEC STOCK CAR CLASS RULES

- Only the mass-produced injection-molded hard plastic bodies are allowed. Bodies too be determined prior to the race and must follow the below conditions:
 - Bodies cannot be cut out in any way.
 - Clip must be attached to the chassis with or without center piece of mounting clip. Stock mounting position only.
 - Bracket may be glued to chassis.
 - All bodies can use glue dots to more firmly secure body to chassis mounts.
- The rear axle and guide pin must be stock. 7/23 gear ratio is allowed. No restriction on front wheels, tires and axle.
- The electrical system must be stock. The use of big foot brushes or twisted endbells is not allowed.
3. The electrical system must be stock or stock replacement wheels.
4. The rear axle and guide pin must be stock. The use of big foot brushes or twisted endbells is not allowed.
5. Only these mass-produced injection-molded hard plastic bodies are allowed. Bodies too be determined prior to the race and must follow the below conditions:
 - Only the rear axle and guide pin must be stock. T/23 gear ratio is allowed. No restriction on front wheels, tires and axle.
 - Clip must be attached to the chassis with or without center piece of mounting clip. Stock mounting position only.
 - Bracket may be glued to chassis.
 - All bodies can use glue dots to more firmly secure body to chassis mounts.
6. The use of glue shall not be allowed on the magnets or to retain the magnets to the chassis.
7. This class is open only to Amateur class drivers [See Amateur eligibility requirements]



18. TRACK AND EQUIPMENT RULES

1. All tracks shall have four or more color-coded lanes in operating condition without any "dead" spots and contain retaining walls of at least one inch in front of the drivers and two and one-half inches everywhere else. Dead spots are locations on the track that contain a different electrical conductivity that is not equal to the rest of the track.
2. Eighteen (18) volt minimum, nineteen (19) volt maximum filtered power supplies, battery or combination thereof shall be used at the HOPRA National Championship Race. Twenty (20) volt filtered power supplies shall be used for Vintage T-Jet class. Twelve and a half (12.5) volt minimum, 13 and a half (13.5) volt maximum filtered power supplies shall be used for Spec Jet class. Power supplies must meet the following specifications of 20 amps minimum per a 4-lane track with 5amps min per lane.
3. All tracks shall be equipped for alligator type hookups and dynamic braking.
4. Repairs and/or modifications to the track shall be approved by the track's owner or the highest-ranking HOPRA official present at the time.
5. All tracks used for HOPRA competition shall have clearly marked track sections for determining the number of sections run at the end of the race.
6. Tire dressings ("glue") of any kind may not be applied to the track in any fashion. The track surface must remain free of anything other than the track surface, environment conditions (i.e., dust), dirt and debris from normal racing conditions. Dressings may not be applied directly to the track in any fashion. Application of dressings to the car in such a manner resulting in the damage of the track, other cars, or the obvious impediment of other cars, is grounds for lap penalties and/or disqualification as determined by the Race Director or other high-ranking HOPRA Official.
 - a. Track Cleaning – HOPRA will take every effort to present the same track conditions to all racers. Therefore, during practice periodically and before each Consi, Semi, Supper Semi, and Mains the track will be dry ragged. This will be done by a HOPRA official or their designee.
 - b. For Gravity competition ONLY - The use of double-sided 3M "sticky" tape will be applied in a main straightaway (placed on each side of the rail for each line). Tape will be replaced before each Consi, Semi, Supper Semi, and Main. During practice Tape will be replaced every 20 minutes. This will be done by a HOPRA official or their designee.
7. Only the track power may be used to power the cars.
 - a. The voltage output of the controller may not exceed the track voltage provided at the White driver's panel post.
 - b. No controller output storage may be used i.e., Capacitors attached to the controller output wire (Black Lead)
 - c. Controllers cannot have batteries.
8. All tracks used for HOPRA competition shall be equipped with reliable, computer scoring system running Slottrax © software. In all situations, the scoring system is considered correct unless it can be proven otherwise, the computer shall be corrected if necessary (such as when a car crosses on the wrong lane). If a lap can be verified by a track marshal as having been missed or added, the Race Director must be notified to correct the count.
9. Each track used for HOPRA National Championship race shall have the Race Director's station located a track side, situated to provide a clear, unobstructed view of the entire racing surface. The Race Director's station shall be equipped with a device to provide the Race Director with direct physical and simultaneous control of track power and segment time. The Race Director's only responsibility shall be to control the racing action on the track. The Race Director shall have no marshaling responsibilities. Another individual shall be employed as Race Scorer/Announcer whenever available manpower permits.

5. SPEC RACER CAR CLASS RULES

Legal chassis are: BSRT G3/G3R/G3RS/G3RSB, Slottech T1/T2/T3, Wizzard Storm/Fusion, Viper V1/V3, RPMs Ghost Cat

1. The chassis must be stock, readily available, "HOPRA Approved" and cannot be machined, sanded or cut except to provide the following:
 - a. Add, remove, or re-add body mounts.
 - b. Reinforce and/or replace pickup tabs.
 - c. Add axle retainer.
2. All magnets shall remain in their stock location. No material or method may be used to restrict the movement of the magnets.
 - a. Only "HOPRA Approved" Compression Molded polymer traction and motor magnets may be used, see SPEC STOCK CAR CLASS RULES for specific manufacturer part numbers.
 - b. The gauss reading of the traction or motor magnet shall not exceed the following criteria. This is taken after a 5 min cool down period and at the lowest point on each magnet as it runs parallel to the rail. Any reading above these figures will be cause for disqualification or rejection at tech.

TRACTION: 1650 gauss maximum MOTOR: 1285 gauss maximum.

3. The guide pin can be a stock replacement. It may be glued in place but shall remain in any one of the stock positions.
4. The armature must be stock or a hot stock. The minimum ohmage allowed shall be 5.80.
5. There are no restrictions on the armature bushings or axles. Ball bearings are not allowed.
6. Gears ratio must be a 7-tooth pinion with a 23-tooth crown gear. No metal gears allowed.
7. There are no restrictions on front wheels, tires and axle.
8. Rear tires shall be any non-coated solid silicone, rubber, or urethane replacement tires. Rear wheels shall be any double or single flanged replacement wheels.
9. Electrical systems shall be stock or stock replacement. Adjustable brush tension is allowed. Physically attaching brushes to springs (using glue or other substance) or spring arm is allowed. Plated parts are allowed. Shunts are not allowed.
10. The use of glue shall not be allowed on the magnets or to retain the magnets to the chassis.





8. A "Track Call" may be invoked by the Race Director if they determine that a hazardous or unfair situation such as lap counter or other track equipment failure, un-marshalable car (cars) that are out of the immediate area or under the track and cannot be replaced quickly, power shall be turned back on as soon as the car is in hand) exists. Power and segment time will be replaced during a "Track Call". During this time, no car repairs, unless authorized by the Race Director or other high ranking HOPro and will result in lap penalties and/or disqualification as determined by the Race Director or other high ranking HOPro. Official Drivers may not declare a "Track Call", or they will be penalized one (1) lap per offense. Except to provide the following:

9. If a driver or marshal damages another car while replacing the car on the track, power to the track shall be turned off to give the offended driver time to put the car back into running order with a time limit on repairs equal to the length of time given to the offending run.

10. The penalty for a de-slot should only be the time it takes to marshal the car(s). A driver shall not be penalized a loss of lap counter misses if their car misses the lap counter due to a de-slot or improper marshaling, nor shall a driver gain a lap by another car laps if their car misses the lap counter to add the deserved lap to the drivers total during or at the end of the segment. Miss the counter, it is up to the race director to add the deserved lap to the drivers total during or at the end of the segment. All magnets shall remain in their stock location. No material or method may be used to restrict the movement of the magnets. Only "HOPro Approved" Compressed Molded polymer motor magnets may be used. See SPEC STOCK CAR a. CLASS RULES for specific manufacturer part numbers.

11. At the conclusion of each race, the cars shall be left on the track where they stopped after the power was shut off until the race director has the right to ask for the removal of a car from the track, which is excessively interfering with other cars, damaging the track and in any manner of unnecessary disrupting the race. The car will only be allowed back on the track after repairs have been made to correct the problem.

12. The Race Director has the right to ask for the removal of a car from the track, which is excessively interfering with other cars, damaging the track and in any manner of unnecessary disrupting the race. The car will only be allowed back on the track after repairs have been made to correct the problem.

13. All Consi. Races will have an equal practice time of between one and two minutes, two minutes of racing per segment, and minimum one and one-half minute breaks between segments.

14. All Semi races will have an equal practice time of between one and three minutes, three minutes of racing per segment, and one and one-half minute breaks between segments.

15. All Super-Semi races will have an equal practice time of between one and four minutes, four minutes of racing segments, and two-minute breaks between segments.

16. The Main will have a practice time (for main event participants only) of a maximum of 15 minutes. Practice times will be determined by the race director. Main will have five minutes of racing per segment, and two and one-half minute breaks between segments.

17. Each race shall begin within 30 seconds after the completion of practice.

5. The guide pin can be a stock replacement. It may be glued in place but shall remain in any one of the stock positions.

6. The armature must be stock or a hot stock. The minimum ohmage allowed shall be 5.80.

7. There are no restrictions on the armature bushings or axles. Ball bearings are not allowed.

8. Gears ratio must be a 7-tooth pinion with a 23-tooth crown gear. No metal gears allowed.

9. There are no restrictions on front wheels, tires and axle.

10. Rear tires shall be any non-coated solid silicone, rubber, or urethane replacement tires. Rear wheels shall be any double or single flanged replacement wheels.

11. Electrical systems shall be stock or stock replacement. Adjustable brush tension is allowed. Physically attaching brushes to spindles (using glue or other substance) or sprung arm is allowed. Plated parts are allowed. Shunts are not allowed.

12. The use of glue shall not be allowed on the magnets or to retain the magnets in the chassis.

17. RACING RULES AND PROCEDURES

1. The order of entry determines starting position in qualifying, the first entry qualifies first.

2. Method for qualifying:

Individually timed laps will be used for qualifying. Each driver qualifies individually and may start on any lane. Drivers are also allowed to switch lanes at any time during their qualifying run. Each driver will be given an equal time to qualify between one and two minutes. A driver's fastest lap time raced will be used to determine their starting position in the race with their back-up time used to break any ties. Each driver should be ready to qualify when the time of the person preceding them has run out. They will be given a maximum of thirty seconds before their qualifying time starts.

3. No "bye" will be issued in qualifying. The car must complete one lap to count as a qualifying time. If the car does not complete one lap, the driver may re-qualify at the bottom of the entry list. After the last scheduled driver, any driver needing to re-qualify must be at the track within two minutes to complete their final attempt. Drivers who don't qualify will start the race at the back of the field. Late entries that miss qualifying will also start the race at the back of the field.

4. There are two systems of racing procedures:

a. The two-bracket system - Drivers are divided into two groups called A and B with the fastest qualifier placed in group A, the second fastest qualifier placed in group B, the third fastest qualifier placed in group A, etc. Initially each race, except the first race in each group is 50% occupied by drivers winning sit-out positions. These races are then filled out by the top finishers making move- ups. The preliminary races in each group are called Consi. Races and the last race in each group is called a Semi, the winners of the Semi plus the drivers with the highest lap totals move up to fill the Main, which is the final race of the event.

b. The four-bracket system - This system may be used if there are 24 or more entries racing on a four- lane track, 36 or more entries racing on a six-lane track, or 48 or more entries racing on an eight- lane track. In this system, drivers are divided into four groups called A, B, C, and D respectively, the fifth fastest qualifier is placed in group A, the sixth fastest qualifier in group B, etc. The races are set up the same way that they are in the two-bracket system and the method of move-ups remains the same as the two-bracket system until the Super-Semis. Then each top finisher from the A and C semis is placed in one Super-Semi called the A-C Super-Semi and each top finisher from the B and D semis is placed in the other Super-Semis called the B-D Super-Semi and then the next highest finishers in all of the semis shall fill out the remaining open positions. The winner of each Super- Semi plus the drivers with the highest lap totals from the Super-Semis move up to fill the Main which is the final race of the event.

5. Initially, lane choices will be determined by qualifying with the fastest qualifier having first choice, etc. Drivers who move up will no longer choose lanes based on qualifying but instead by their order of finish in the previous race. These drivers will choose lanes after those winning sit-out positions.

6. In all HOPRA events, each driver will have the opportunity to drive on all lanes during the race. This shall be achieved by drivers moving to adjacent lanes in a systematic manner (it is recommended that drivers move from the outer-most lane to the inner-most lane). A race will consist of as many prescribed segments as lanes used.

7. During lane changes, the power to the track should be off. During this lane change period, the driver is responsible for changing their lane tape and replacing the car to the track at the location it stopped at the end of the previous segment. Marshals or others shall not remove any car from the track after the conclusion of a segment unless specifically authorized to do so by the driver of that car. Marshals shall assist drivers in making lane changes when asked to do so. Replacing a car in an advantageous position will result in lap penalties and/or disqualification as determined by the Race Director or other high ranking HOPRA Official. When a car is removed from the track during racing, the same conditions apply.

7. VINTAGE T-JET CAR CLASS RULES

Legal chassis and top plates are: Any Original Aurora thunder-jet, T-Dash, Wizz-Jet - Blizzard is NOT legal

All General rules are applicable to this class and shall be followed.

1. Car including body must weigh between 19 and 24 grams
2. Electrical system must be copper material and be stock or stock replacement. Plated chassis electrical components or pickup shoes parts are not allowed. Brush tensioners and shoe hanger plates may be bent to adjust shoe tension. Shunts are not allowed.
3. Chassis holes may be closed or opened for proper clearance.
4. Brushes must be copper and may be scored with an X or line.
5. Any stock T-Jet pancake armature that is Aurora 2 lam, Dash 2 or 3 lam, or OS3 is allowed. The armature may be balanced and trued with a minimum 16.0 ohms (measured pole to pole with armature removed from car and checked after a 5-minute cool down). Washers or spacers are allowed on the armature.
6. Magnets must be ceramic and readily available. Magnets may be sanded to fit the chassis. The distance between the magnets must be a minimum of .700". Any nonmagnetic materials may be employed to restrict the movement of the magnets and may be glued to the magnet. Material is not allowed under or on top of magnets.
7. Any solid brass stock or stock replacement gears may be used and must be a minimum of .045" thick. Only 14T (motor pinion), 24T(idler), 24T(driven), 9T (drive pinion) are allowed. Any crown gear is allowed and must be stock or stock replacement, 15T, and installed in the car the diameter must not be smaller than .300". Crown gears may be trimmed or spaced to adjust for proper gear mesh.
8. Gears cannot be cut, lightened, drilled, chamfered, or relieved. Polishing/deburring is allowed. Gears may be glued or soldered on the shaft.
9. There are no restrictions on axles, drive gear shafts, wheels or tires. Rear wheel weights are not allowed.
10. There are no restrictions on front ends except they must be stock or stock replacement and may be spaced on the outside of the frame rail only.
11. Pickup shoes shall be stock or stock replacement. Ski shoes are not allowed.
12. Pickup shoes springs may be any material and must be cylindrical in shape.
13. Gear plate rails may be trimmed to the plane of the top plate.
14. The guide pin must be plastic material stock or stock replacement. It may be countersunk and glued in place but shall remain in the stock position.
15. With exception of the guide pin location, the use of glue shall not be allowed on the chassis or top plate.



1. All bodies shall resemble a 1:1 or concept car and originally manufactured with mounting posts in the front and back for 2 screw mounting. No open wheel bodies are allowed. All bodies must be mounted with 2 screws.

2. Body must be plastic from injection molding, resin cast, or 3D printed and cannot contain any ballast, filters (other than pigment), added weight, or magnetism.

3. The body must cover the front and rear of the chassis when viewed from above.

4. When viewed from the back, front, or side, the line in upper surface of the top plate (not including rails) must be shielded by the body.

5. No additional weight may be added to bodies. Glue is allowed for repairs and windshield installation.

6. Bodies may be repaired, lightened, and lowered as long as they fit the existing rules.

7. Bodies cannot be manipulated by heat to intentionally warp.

8. Wheel-wells may be opened but must not be exaggerated past a 1/8" size around the tire from the side.

9. Complete front windshields are required and must be molded, vacuum formed, or injection molded plastic. Side and/or rear windows may be removed.

9. PROTESTS

1. The use of abusive language and/or misconduct by drivers toward marshals and/or other drivers will not be tolerated at the race site. A verbal warning will be given by the HOProA director to the violator on their first offense. Any driver that marshals their own car shall receive a lap penalty or be disqualified if another driver's car is damaged.
2. Un-sportsmanlike conduct on the part of any participant (including bystanders and/or spectators) at a HOProA event may result in lap penalties and/or disqualification as determined by the Race Director or other high-ranking HOProA Officials.
3. All drivers must take turns serving as team marshals unless otherwise authorized by the Race Director. Substitute marshals may result in the participant being prohibited from future HOProA activities as determined by a vote of the HOProA National Executive Committee.
4. Drivers will be no driver changes. Drivers shall use the car they submit to tech.
5. A line minimum of 1' (one foot) from the track table shall be present in front of which driver shall stand. Special accommodations can be made.
6. Any driver is eligible to compete in the Unlimited, Polymer Modified or Modified class at the HO Nationals. Drivers may enter only one Super Stock Class, either Amateur or Pro.
7. Drivers Amateur class eligibility for the HO Nationals.
8. Any unknown driver wishing to enter the Amateur class will be given the benefit of the doubt and allowed to compete.
9. Protests shall be made in writing to the highest-ranking National Executive Committee member at the race within one hour after the occurrence. A fee equal to the protest's entry fee must accompany the protest. The protest will be acted upon by the National Executive Committee members present and their decision will be final. If the protest is denied the protest fee will be returned. A protest must follow these guidelines to be considered valid. If a protest is denied the protest fee will go to the HOProA National Organization.



16. DRIVER RULES

1. The use of abusive language and/or misconduct by drivers toward marshals and/or other drivers will not be tolerated at the race site. A verbal warning will be given by the HOProA director to the violator on their first offense. Any driver that marshals their own car shall receive a lap penalty or be disqualified if another driver's car is damaged.
2. Un-sportsmanlike conduct on the part of any participant (including bystanders and/or spectators) at a HOProA event may result in lap penalties and/or disqualification as determined by the Race Director or other high-ranking HOProA Officials.
3. All drivers must take turns serving as team marshals unless otherwise authorized by the Race Director. Substitute marshals may result in the participant being prohibited from future HOProA activities as determined by a vote of the HOProA National Executive Committee.
4. Drivers will be no driver changes. Drivers shall use the car they submit to tech.
5. A line minimum of 1' (one foot) from the track table shall be present in front of which driver shall stand. Special accommodations can be made.
6. Any driver is eligible to compete in the Unlimited, Polymer Modified or Modified class at the HO Nationals. Drivers may enter only one Super Stock Class, either Amateur or Pro.
7. Drivers Amateur class eligibility for the HO Nationals.
8. Any unknown driver wishing to enter the Amateur class will be given the benefit of the doubt and allowed to compete.
9. Protests shall be made in writing to the highest-ranking National Executive Committee member at the race within one hour after the occurrence. A fee equal to the protest's entry fee must accompany the protest. The protest will be acted upon by the National Executive Committee members present and their decision will be final. If the protest is denied the protest fee will be returned. A protest must follow these guidelines to be considered valid. If a protest is denied the protest fee will go to the HOProA National Organization.

15. BEST APPEARING RACE CAR RULES AND PROCEDURES

1. The Best Appearing Race Car competition is, by definition, "A competition to determine the best-looking cars that are entries in a racing event". Before any entry may receive a Best Appearing Race Car Award, he or she shall also be an entry for the appropriate racing class, comply with all requirements of Technical Inspection for the Class, complete a qualifying run, and participate to the fullest extent possible in the races scheduled for that class. Obvious "sandbagging" during racing competition in order to minimize the chances for damage to the car is not in the spirit of the Best Appearing Race Car competition and may result in disqualification from the Best Appearing Race car competition as determined by the Race Director or other high ranking HOPRA Official.
2. Each Best Appearing Race Car entry shall compete during qualifying and racing in the same configuration as presented for Best Appearing Race Car judging. A separate race body is specifically not allowed.
3. For Best Appearing Race Car judges shall be chosen by the Race Promoter from among those not entering the Best Appearing Race Car competition. Each judge shall be from a different region of the country. The Best Appearing Race Car judge shall assign points to the Best Appearing Race Car cars individually. The highest and lowest of the four judges' individual scores will be dropped, and the sum of the two remaining scores shall be an entry's final Best Appearing Race Car points total. The maximum possible score per judge is 50 points and the maximum possible score per entry is 100 points.
4. In the case of a tie after judging, the high and low scores shall be used as the tiebreaker. If a tie still exists, then the racer's finishing position in their class shall be used as the tiebreaker. If a tie still exists, then the racer's qualifying position in their or her class shall be used as the tiebreaker. If a tie still exists, the National Director shall appoint a panel of Media Representatives, or other impartial individuals as can be secured, and empower this panel with the responsibility to break any ties that remain.
5. Appearing Race Car judges shall use the following points system to determine Best Appearing Race Car placing:
 - a. Exterior Detail (0-15 points) - Areas to be considered include numbering, lettering, decals, etc.
 - b. Added physical details and interior details are specifically excluded from judging as outlined above in Best Appearing Race Car #3.
 - c. Paint and Finish (0-15 points) - Quality of the paint, neatness of the application of the paint to the body and evenness of the coat will be considered here.
 - d. Overall Impression (0-20 points) - Realism and the general aesthetic quality of the car will be considered here. Scale replicas and original paint schemes of equal quality shall be given equal consideration.
6. Once an individual car has won any Best Appearing Race Car event it shall become ineligible to compete in another Best Appearing Race Car event.



8. SUPER STOCK CAR CLASS RULES

Legal chassis are: BSRT G3/G3R/G3RS/G3RSB, Mattel/Tyco 440 X2, Micro Speedworks T+, Slottech T1/T2/T3 and T1X, Wizzard-Patriot P2/P3/Scorpion/Storm/Storm CH22/Fusion, Viper V1/V3, RPMs Ghost Cat

1. The chassis must be stock, readily available, "HOPRA Approved" and cannot be machined, sanded or cut except to provide the following:
 - a. Add, remove or re-add body mounts.
 - b. Reinforce and/or replace pickup tabs.
 - c. Add adjustable Brush tension.
 - d. Add axle retainer.
2. The guide pin can be a stock replacement part. It may be glued in place but shall remain in any one of the stock positions.
3. All magnets used shall be stock or stock replacement ceramic "HOPRA Approved" and cannot be cut. The gauss reading of the traction or motor magnet shall not exceed the following criteria. This is taken after a 5 min cool down period and at the lowest point on each magnet as it runs parallel to the rail. Any reading above these figures will be cause for disqualification or rejection at tech.

TRACTION: 1500 gauss maximum MOTOR: 1000 gauss maximum.
4. Mattel/Tyco 440 X2 traction magnets must be of matching polarity.
5. All magnets shall remain in their stock location. No material or method may be used to restrict the movement of the magnets.
6. Any flux collectors used shall be stock and shall remain in their stock location and cannot be modified.
7. The armature must be stock or a hot stock. The minimum ohmage allowed shall be 5.80.
8. Axle bushings are not allowed unless they are stock.
9. There are no restrictions on the armature bushings, gears, axles, wheels and tires. Ball bearings are not allowed.
10. Electrical systems shall be stock or stock replacement. Adjustable brush tension is allowed. Physically attaching brushes to springs (using glue or other substance) or spring arm is allowed. Plated parts are allowed. Shunts are not allowed.
11. The use of glue shall not be allowed on the magnets or to retain the magnets to the chassis.





14. CONCOURS D'ELEGANCE RULES AND PROCEDURES

Legal chassis are: BSR/T2/G3/GR3S/G3RS, Matter/Tyc0 440X2, Sotetech Panther/Parther 02, Thundercat T3, Tix, ToMy AX Super G+, Wizzard Storm/Fusion, Viper V1/V3, PMs GhosT Cat

1. The chassis must be stock, readily available, "HOPRA Approved" and cannot be machined, sanded or cut except to provide the following:

- Concours entries shall be in running order when entered and shall be required to run one lap on the designated track only. Cars may be entered may be separate entries. Any one making a Concours entry per person shall be allowed per event.
- All Concours entries shall consider a legal entry. Concours entries shall also comply with all requirements set forth in the Unlimited Car Class Rule, V.

2. The following:

- Concours entries may exceed the maximum width and length restrictions of General Rules #14-16 provided that exceeding these dimensions is appropriate in constructing and HO scale representation of the type of vehicle entered. (i.e., A top fuel dragster may exceed the maximum length of three inches.)
- Added air control devices shall be allowed.

3. Concours judges shall be chosen by the Race Promoter from among those not entering the Concours competition. Each judge shall be a different region of the country. The Concours judges shall assign points to the Concours cars individually. The highest and lowest of the four judges, individual scores will be dropped, and the sum of the two remaining scores shall be an entry. Final Concours points total. The maximum possible score per judge is 50 points and the maximum possible score per entry is 100 points.

4. In the case of a tie after judging, the two high and low scores shall be used as the tiebreaker. If a tie still exists, the National Director shall appoint a panel of Media Representatives, or other impartial individuals as can be secured, and empower this panel with the responsibility to break any ties that remain.

5. Concours judges shall use the following points system to determine Concours placing:

- Internal Detail (0-10 points) - General appearance, neatness, neatness, neatness, neatness, neatness, neatness, neatness, neatness, neatness.
- Exterior Detail (0-10 points) - Areas to be considered include mirrors, numbering, lettering, details, headlamps, bumpers, angles, and any other exterior detail.
- Paint and Finish (0-10 points) - Quality of the paint, neatness of the application of the paint to the body and evenness of the coat will be considered here.
- Chassis (0-5 points) - General appearance of the work done and neatness will be considered here.
- Overall Impression (0-15 points) - Realism and the general aesthetic quality of the car will be considered here.

6. Once an individual car has won any Concours event, it shall become ineligible to compete in another Concours event.

7. There are no restrictions on the guide pin, gears, or axles.

8. There are no restrictions on the armature bushings (may be glued in). Ball bearings are not allowed.

9. Rear tires shall be any non-cast solid silicone, rubber, or urethane replacement tires. Rear wheels shall be any double or single flanged replacement wheels.

10. Rear tires shall be any non-cast solid silicone, rubber, or urethane replacement tires. Rear wheels shall be any double or single flanged replacement wheels.

11. Electrical systems shall be stock or stock replacement. Adjustable brush tension is allowed. Physically attaching brushes to springs (using glue or other substance) or spring arm is allowed. Plated parts are allowed. Shims are not allowed.

12. The armature must be stock or a hot stock. The minimum ohmage allowed shall be 2.30.

13. The use of glue shall not be allowed on magnets or to retain the magnets to the chassis. Other non-magnetic materials may be employed to retain the magnets to the chassis. Any chassis clip used to hold the car together must not touch the magnets or affect the magnetic field.

14. The use of glue shall not be allowed on magnets or to retain the magnets to the chassis. Any chassis clip used to hold the car together must not touch the magnets or affect the magnetic field.

15. TRACTION: 2230 gauss maximum, MOTOR: 1775 gauss maximum.

9. MODIFIED CAR CLASS RULES

12. UNLIMITED CAR CLASS RULES

1. General rules 1 through 13 are not applicable to this class. General rules 14 through 28 are applicable and shall be followed.
2. There are no restrictions on chassis cutting. Scratch built chassis' will be allowed.
3. There are no restrictions on the type of magnets, magnet material, position of magnets, or number of magnets. Cobalt or Rare Earth type magnets will be allowed.
4. There are no restrictions on the armature, bearings, gears, wheels, axles, tires, guide pin and electrical system.
5. Any car or device, which is considered hazardous to the track, the marshals, other drivers or other cars, shall be declared illegal and not allowed to run.

13. GRAVITY CAR CLASS RULES

1. General Rules 1 through 13 are not applicable to this class. General Rules 14 through 28 are applicable and shall be followed.
2. There are no restrictions on chassis cutting. Scratch-built chassis are allowed.
3. Magnets are restricted to two motor magnets only. There are no restrictions to the type of magnets, magnet material, or position of the magnets. Cobalt or Rare Earth type magnets are allowed.
4. There are no restrictions on the armature, bearings, gears, wheels, axles, tires, guide pin and electrical system.
5. The car must pass the Lift Test, unless the track being raced on has non-magnetic rails.

Lift Test defined as the following:

- a. The lift testing device is a 5/16 piece of O-1 drill rod that is 1.312 inches long and has .004 of additional non-magnet surface. Typically, this additional non-magnet surface can be achieved with layers of tape.
- b. To pass inspection, the lift testing device is placed anywhere on the bottom of the car, in a horizontal position, and cannot be held by the car. Testing may require removal of the pick-ups or tires. The tech inspector will lay the pin flat on the table, lower the car to the pin and lift. The lowering, touch of pin and lift is one continuous motion. If necessary, this method will be performed 3 times by the same tech inspector before and after the race unless extenuating circumstance arise.

6. Any car or device, which is considered hazardous to the track, the marshals, other drivers or other cars, shall be declared illegal and not allowed to run.

10. COMPRESSION MOLDED POLYMER MODIFIED CAR CLASS RULES

Legal chassis are: BSRT T2/G3/G3R/G3RS/G3RSB, Mattel/Tyco 440x2, Slottech Panther/Panther 02, Thundercat T3, T1X, Tomy AFX Super G+, Wizzard Storm/Fusion, Viper V1/V3, RPMs Ghost Cat

1. The chassis must be stock, readily available, "HOPRA Approved" and cannot be machined, sanded or cut except to provide for the following:
 - a. Add, remove or re-add body mounts.
 - b. Mount any guide pin holder - guide pin shall remain in any one of the stock positions.
 - c. Add armature bushings or ball bearings.
 - d. Drill or cut holes for adjustable brush tension.
 - e. The bottom surface of the chassis and bulkheads may be sanded flat. However, the bottom bulkhead tabs shall remain naturally connected to the end bells.
 - f. The pickup retaining tabs on the chassis may be reinforced and/or replaced in their stock position.
 - g. Add rear axle retainer.
 - h. Add bulkhead/magnet clip retaining screws.
2. All magnets shall remain in their stock location.
 - a. Only "HOPRA Approved" compression molded polymer magnets may be used, see below for specific manufacturer part numbers. Magnets may be sanded flat on the bottom surface only, so they are flush with the bottom surface of the chassis and bulkheads.
 - b. The gauss reading of the traction or motor magnet shall not exceed the following criteria. This is taken after a 5 min cool down period and at the lowest point on each magnet as it runs parallel to the rail. Any reading above these figures will be cause for disqualification or rejection at tech.

TRACTION: 2230 gauss maximum MOTOR: 1775 gauss maximum

"HOPRA Approved" Compression Molded Polymer Magnets for Polymer Modified Car

Magnets are listed by magnet manufacturer and may be used in all chassis adhering to class rules

Manufacturer	Part #	Description
BSRT	#272	G-Force Traction
	#263	G-Force Motor
	#271	G-Force Traction
	#278	G-Force Traction
	#277	G-Force H-D Motor
	#290	G-Force Motor
	#284	G-Force Traction
	#276	G-Force H-D Motor
	#292	G-Force Motor
	#286	G-Force Traction
Slottech	#64	T3 Motor
	#81	Motor
	#81C	Motor
	#86	Traction
	#86C	Traction
	#62-1	PolyMax Motor
	#62-2	PolyMax Motor LW
	#67	PolyMax Traction
	#68	MegaFlux Traction

**Continued next page*





11. NEO MODIFIED CAR CLASS RULES

Legal chassis are: BSRT T2/G3/G3R/G3RS, Matel/Tyc0 440 X2, Micro Speedworks T+, Slottech Panther/Panther, 02/Tundercraft T1 and T1X, Tomy AX Super G+, Wizzard-Patrol P2/P3/Scorpio/Storm CH22/Fusion, Viper V1/V3,

1. The chassis must be stock, readily available, "HOPro Approved" and cannot be machined, sanded or cut except to provide for the following:

- a. Add, remove or re-add body mounts.
- b. Mount any guide pin holder - guide pin shall remain in any one of the stock positions.
- c. Add motor bushings.
- d. Drill or cut holes for adjustable brush tension.
- e. The bottom surface of the chassis and bulkheads may be sanded flat. However, the bottom bulkhead tabs shall remain relatively connected to the end bulkheads.
- f. The pickup retainer tabs on the chassis may be reinforced and/or replaced in their stock position.
- g. Add rear axle retainer.
- h. Add front axle retainer.
- i. Add bulkhead/magnet clip retainer screws.
- j. Add any stock or stock replacement front bumper.
- 2. All magnets shall remain in their stock location.

3. Rear axle bushings are allowed for the approved chassis only. Ball bearings are not allowed in the rear axle.

4. The use of glue shall not be allowed on the magnets or to retain the magnets to the chassis. Other non-magnetic materials may be employed to restrict the movement of the magnets. Any clip used to hold the car together must be non-magnetic only.

5. Any type of armature shall be legal.

6. Electrical systems shall be stock or stock replacement parts. Adjustable brush tension is allowed. Physically attaching brushes to springs (using glue or other substance) or spring arm is allowed. Plated parts are allowed. Shunts are allowed.

7. There are no restrictions on the armature bushings/ball bearings (may be glued in), guide pin, wheels, tires, gears and axles.

8. There are no restrictions on the type of magnet material, cobalt, rare earth or polymer are allowed.

Magnets are listed by magnet manufacturer and may be used in all chassis adhering to class rules

"HOPro Approved" Compressed Molded Polymer Magnets for Polymer Modified Car-Continued

Manufacturer	Part #	Description	Slottech	Wizzard	Viper Scale Racing	RPMs
Slottech	#66	Polymer Motor	W560	W561	W200	RPM-HD-LD10
	#61	Polymer Traction	Stock Storm Motor	Stock Storm Motor	High Traction Motor	Hyper-Force HD Motor
			High Level Storm Traction	High Level Storm Traction	High Traction Motor	RPM-HD-HM10
			MH66	MH67	12006	RPM-HD-10-T
			Stock Storm Traction	Stock Storm Traction	Motor	Hyper-Force Traction
					12005	RPM-HD-10-T
					12002	Hyper-Force Motor
					12003	Hyper-Force Motor
					12004	Hyper-Force Motor
					12005	Hyper-Force Motor
					12006	Hyper-Force Motor
					12007	Hyper-Force Motor
					12008	Hyper-Force Motor
					12009	Hyper-Force Motor
					12010	Hyper-Force Motor
					12278	Hyper-Force Motor
					12279	Hyper-Force Motor
					12280	Hyper-Force Motor
					12281	Hyper-Force Motor
					12282	Hyper-Force Motor
					12283	Hyper-Force Motor
					12284	Hyper-Force Motor
					12285	Hyper-Force Motor
					12286	Hyper-Force Motor
					12287	Hyper-Force Motor
					12288	Hyper-Force Motor
					12289	Hyper-Force Motor
					12290	Hyper-Force Motor
					12291	Hyper-Force Motor
					12292	Hyper-Force Motor
					12293	Hyper-Force Motor
					12294	Hyper-Force Motor
					12295	Hyper-Force Motor
					12296	Hyper-Force Motor
					12297	Hyper-Force Motor
					12298	Hyper-Force Motor
					12299	Hyper-Force Motor
					12300	Hyper-Force Motor
					12301	Hyper-Force Motor
					12302	Hyper-Force Motor
					12303	Hyper-Force Motor
					12304	Hyper-Force Motor
					12305	Hyper-Force Motor
					12306	Hyper-Force Motor
					12307	Hyper-Force Motor
					12308	Hyper-Force Motor
					12309	Hyper-Force Motor
					12310	Hyper-Force Motor
					12311	Hyper-Force Motor
					12312	Hyper-Force Motor
					12313	Hyper-Force Motor
					12314	Hyper-Force Motor
					12315	Hyper-Force Motor
					12316	Hyper-Force Motor
					12317	Hyper-Force Motor
					12318	Hyper-Force Motor
					12319	Hyper-Force Motor
					12320	Hyper-Force Motor
					12321	Hyper-Force Motor
					12322	Hyper-Force Motor
					12323	Hyper-Force Motor
					12324	Hyper-Force Motor
					12325	Hyper-Force Motor
					12326	Hyper-Force Motor
					12327	Hyper-Force Motor
					12328	Hyper-Force Motor
					12329	Hyper-Force Motor
					12330	Hyper-Force Motor
					12331	Hyper-Force Motor
					12332	Hyper-Force Motor
					12333	Hyper-Force Motor
					12334	Hyper-Force Motor
					12335	Hyper-Force Motor
					12336	Hyper-Force Motor
					12337	Hyper-Force Motor
					12338	Hyper-Force Motor
					12339	Hyper-Force Motor
					12340	Hyper-Force Motor
					12341	Hyper-Force Motor
					12342	Hyper-Force Motor
					12343	Hyper-Force Motor
					12344	Hyper-Force Motor
					12345	Hyper-Force Motor
					12346	Hyper-Force Motor
					12347	Hyper-Force Motor
					12348	Hyper-Force Motor
					12349	Hyper-Force Motor
					12350	Hyper-Force Motor
					12351	Hyper-Force Motor
					12352	Hyper-Force Motor
					12353	Hyper-Force Motor
					12354	Hyper-Force Motor
					12355	Hyper-Force Motor
					12356	Hyper-Force Motor
					12357	Hyper-Force Motor
					12358	Hyper-Force Motor
					12359	Hyper-Force Motor
					12360	Hyper-Force Motor
					12361	Hyper-Force Motor
					12362	Hyper-Force Motor
					12363	Hyper-Force Motor
					12364	Hyper-Force Motor
					12365	Hyper-Force Motor
					12366	Hyper-Force Motor
					12367	Hyper-Force Motor
					12368	Hyper-Force Motor
					12369	Hyper-Force Motor
					12370	Hyper-Force Motor
					12371	Hyper-Force Motor
					12372	Hyper-Force Motor
					12373	Hyper-Force Motor
					12374	Hyper-Force Motor
					12375	Hyper-Force Motor
					12376	Hyper-Force Motor
					12377	Hyper-Force Motor
					12378	Hyper-Force Motor
					12379	Hyper-Force Motor
					12380	Hyper-Force Motor
					12381	Hyper-Force Motor
					12382	Hyper-Force Motor
					12383	Hyper-Force Motor
					12384	Hyper-Force Motor
					12385	Hyper-Force Motor
					12386	Hyper-Force Motor
					12387	Hyper-Force Motor
					12388	Hyper-Force Motor
					12389	Hyper-Force Motor
					12390	Hyper-Force Motor
					12391	Hyper-Force Motor
					12392	Hyper-Force Motor
					12393	Hyper-Force Motor
					12394	Hyper-Force Motor
					12395	Hyper-Force Motor
					12396	Hyper-Force Motor
					12397	Hyper-Force Motor
					12398	Hyper-Force Motor
					12399	Hyper-Force Motor
					12400	Hyper-Force Motor
					12401	Hyper-Force Motor
					12402	Hyper-Force Motor
					12403	Hyper-Force Motor
					12404	Hyper-Force Motor
					12405	Hyper-Force Motor
					12406	Hyper-Force Motor
					12407	Hyper-Force Motor
					12408	Hyper-Force Motor
					12409	Hyper-Force Motor
					12410	Hyper-Force Motor
					12411	Hyper-Force Motor
					12412	Hyper-Force Motor
					12413	Hyper-Force Motor
					12414	Hyper-Force Motor
					12415	Hyper-Force Motor
					12416	Hyper-Force Motor
					12417	Hyper-Force Motor
					12418	Hyper-Force Motor
					12419	Hyper-Force Motor
					12420	Hyper-Force Motor
					12421	Hyper-Force Motor
					12422	Hyper-Force Motor
					12423	Hyper-Force Motor
					12424	Hyper-Force Motor
					12425	Hyper-Force Motor
					12426	Hyper-Force Motor
					12427	Hyper-Force Motor
					12428	Hyper-Force Motor
					12429	Hyper-Force Motor
					12430	Hyper-Force Motor
					12431	Hyper-Force Motor
					12432	Hyper-Force Motor
					12433	Hyper-Force Motor
					12434	Hyper-Force Motor
					12435	Hyper-Force Motor
					12436	Hyper-Force Motor
					12437	Hyper-Force Motor
					12438	Hyper-Force Motor
					12439	Hyper-Force Motor
					12440	Hyper-Force Motor
					12441	Hyper-Force Motor
					12442	Hyper-Force Motor
					12443	Hyper-Force Motor
					12444	Hyper-Force Motor
					12445	Hyper-Force Motor
					12446	Hyper-Force Motor
					12447	Hyper-Force Motor
					12448	Hyper-Force Motor
					12449	Hyper-Force Motor
					12450	Hyper-Force Motor
					12451	Hyper-Force Motor
					12452	Hyper-Force Motor
					12453	Hyper-Force Motor
					12454	Hyper-Force Motor
					12455	Hyper-Force Motor
					12456	Hyper-Force Motor
					12457	Hyper-Force Motor
					12458	Hyper-Force Motor
					12459	Hyper-Force Motor
					12460	Hyper-Force Motor
					12461	Hyper-Force Motor
					12462	Hyper-Force Motor
					12463	Hyper-Force Motor
					12464	Hyper-Force Motor
					12465	Hyper-Force Motor
					12466	Hyper-Force Motor
					12467	Hyper-Force Motor
					12468	Hyper-Force Motor
					12469	Hyper-Force Motor
					12470	Hyper-Force Motor
					12471	Hyper-Force Motor
					12472	Hyper-Force Motor
					12473	Hyper-Force Motor
					12474	Hyper-Force Motor
					12475	Hyper-Force Motor
					12476	Hyper-Force Motor
					12477	Hyper-Force Motor
					12478	Hyper-Force Motor
					12479	Hyper-Force Motor
					12480	Hyper-Force Motor
					12481	Hyper-Force Motor
					12482	Hyper-Force Motor
					12483	Hyper-Force Motor
					12484	Hyper-Force Motor
					12485	Hyper-Force Motor
					12486	Hyper-Force Motor
					12487	Hyper-Force Motor
					12488	Hyper-Force Motor
					12489	Hyper-Force Motor
					12490	